



Seal & Bond Sealtrans

FLEXIBLE DECORATIVE SEALANT

- ✓ Safe to use on natural stone.
- ✓ Brilliant, dirt-repelling joints with excellent UV-resistance.

Technical Info

Character: elastic synthetic rubber based on polysiloxanes.

Consistency: paste-like.

Colour: transparant - brilliant.

Shrinkage: according to DIN 52451 < 1%.

Sagging out: according to ISO 7390 less than 1 mm.

Max. permitted tranformation: 25% - durable.

Shore hardness W: 24 Shore A - according ISO 868.

Tensile strength: 130 N/cm².

Elongation at rupture: 600%.

E-modul: 100% 0.3 mPa.

UV-resistance: excellent.

Water resistance: excellent, also seawater resistant.

Fungicidal: according to ISO 846.

Painting: Can not be painted.

Curing at 23°C and 50% R.H.: 2 mm after 24 hrs.

Thermal stability: -45°C to +155°C.

Volatile organic compounds (VOC): 0,00%.

Organic solvents: 0,00%.

Application temperature: from +5°C up to +40°C.

Shelf life: 12 months, keep dry, cool and frost-free.

Safety measures: consult the Safety Data Sheet.

Packing

Seal & Bond Sealtrans transparent - cartridge 310ml	539096000
Seal & Bond Sealtrans black - cartridge 310ml	539016000
Seal & Bond Sealtrans white - cartridge 310ml	539026000

Product [STS]

Characteristics

Seal & Bond Sealtrans is a versatile synthetic rubber polymer for permanently elastic sealing based on siloxanes. The variable color pigmentation and its transparency provide an aesthetic effect in the finishing of decorative elements. Adheres without primer to most materials.

Applications

- applicable where elastic, transparent joints are required.
- very appropriate for sealing "problematic" surfaces such as natural stone and acrylate, due to its composition free of plasticizers.
- ideal transparent sealant for use in interior construction, verandas, windows and doors, kitchens and bathrooms as well as in general maintenance.
- excellent adherence to most surfaces found in the building industry, e.g.: natural stone, brick, concrete, ceramics, enamel, acrylate, porcelain, metals, glass, soft and hard wood ... with the exception of PE - PP - Teflon and bitumen.

Seal & Bond Sealtrans transparent - sausage 310
ml

539097000

Use

- Apply on a clean and dry surface, above 5 ° C.
 - Finishing seams with Novatio Seal & Bond Finisher.
- Use Seal & Bond Special Primer on PE, PP, Teflon and polyolefin. Not paintable.

